


PROGRAMMABLE SHUNT REGULATOR

The LM431 Series are three-terminal adjustable regulator series with a guaranteed thermal stability over applicable temperature ranges. The output voltage may be set to any value between V_{REF} (approximately 2.5 volts) and 36 volts with two external resistors. These devices have a typical dynamic output impedance of 0.2Ω . Active output circuitry provides a very sharp turn-on characteristic, making these devices excel lent replacement for zener diodes in many applications.

FEATURES


- Programmable output voltage to 36 volts
- Low dynamic output impedance 0.20 typical
- Sink current capability of 1.0 to 100mA
- Equivalent full-range temperature coefficient of 50ppm/ $^{\circ}\text{C}$ typical
- Temperature compensated for operation over full rated operating temperature range
- Low output noise voltage
- Fast turn-on response



ORDERING INFORMATION

Device	Operating Temperature	Package
LM431ACZ (TL431CLP) (KA431Z)	-25 ~ + 85 $^{\circ}\text{C}$	TO-92
TL431CP (KA431)	-25 ~ + 85 $^{\circ}\text{C}$	8 DIP
LM431ACM (TL431CD) (KA431D)	-25 ~ + 85 $^{\circ}\text{C}$	8 SOP
LM431BCZ (TL431ACLP) (KA431AZ)	-25 ~ + 85 $^{\circ}\text{C}$	TO-92
LM431BCM (TL431ACD) (KA431AD)	-25 ~ + 85 $^{\circ}\text{C}$	8 SOP
LM431CCZ (KA431LZ)	-25 ~ + 85 $^{\circ}\text{C}$	TO-92

BLOCK DIAGRAM



Rev. C

ABSOLUTE MAXIMUM RATINGS

(Operating temperature range applies unless otherwise specified.)

Characteristic	Symbol	Value	Unit
Cathode Voltage	V_{KA}	37	V
Cathode current Range (Continuous)	I_{KA}	-100~ + 150	mA
Reference Input Current Range	I_{REF}	0.05~ + 10	mA
Power Dissipation D, Z Suffix Package N Suffix Package	P_D	770 1000	mW mW
Operating Temperature Range	T_{OPR}	-25 ~ + 85	°C
Storage Temperature Range	T_{STG}	-65 ~ + 150	°C

RECOMMENDED OPERATING CONDITIONS




Characteristic	Symbol	Min	Typ	Max	Unit
Cathode Voltage	V_{KA}	V_{REF}		36	V
Cathode Current	I_{KA}	1.0		100	mA

ELECTRICAL CHARACTERISTICS ($T_A = + 25^\circ\text{C}$, unless otherwise specified)

Characteristic	Symbol	Test Conditions	TL431			TL431A			TL431L			Unit
			Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
Reference Input Voltage	V_{REF}	$V_{KA}=V_{REF}, I_{KA}=10\text{mA}$	2.440	2.495	2.550	2.470	2.495	2.520	2.482	2.495	2.508	V
Deviation of Reference Input Voltage Over-Temperature (Note 1)	DV_{REF}/DT	$V_{KA}=V_{REF}, I_{KA}=10\text{mA}$ $T_{MIN} \leq T_A \leq T_{MAX}$		4.5	17		4.5	17		4.5	17	mV
Ratio of Change in Reference Input Voltage to the Change in Cathode Voltage	DV_{REF}/DI_{KA}	$I_{KA}=10\text{mA}$ $DV_{KA}=10\text{V}-V_{REF}$		- 10	- 2.7		- 1.0	- 2.7		- 1.0	- 2.7	mV/W
		$I_{KA}=36\text{V}-10\text{V}$		- 0.5	- 2.0		- 0.5	- 2.0		- 0.5	- 2.0	
Reference Input Current	I_{REF}	$I_{KA}=10\text{mA}, R_1=10\text{K}\Omega, R_2=\infty$		1.5	4		1.5	4		1.5	4	μA
Deviation of Reference Input Current Over Full Temperature Range	DI_{REF}/DT	$I_{KA}=10\text{mA}, R_1=10\text{K}\Omega, R_2=\infty$ $T_A = \text{Full Range}$		0.4	1.2		0.4	1.2		0.4	1.2	μA
Minimum Cathode Current for Regulation	$I_{KA(MIN)}$	$V_{KA}=V_{REF}$		0.45	1.0		0.45	1.0		0.45	1.0	mA
Off - Stage Cathode Current	$I_{KA(OFF)}$	$V_{KA}=36\text{V}, V_{REF}=0$		0.05	1.0		0.05	1.0		0.05	1.0	μA
Dynamic Impedance (Note 2)	Z_{KA}	$V_{KA}=V_{REF}, I_{KA}=1 \text{ to } 100\text{mA}$ $f = 1.0\text{K}\Omega$		0.15	0.5		0.15	0.5		0.15	0.5	Ω

 $T_{MIN} = -25^\circ\text{C}, T_{MAX} = +85^\circ\text{C}$

TEST CIRCUITS

Fig. 1 Test Circuit for $V_{KA}=V_{REF}$ Fig. 2 Test Circuit for $V_{KA} \geq V_{REF}$ Fig. 3 Test Circuit for $I_{KA(OFF)}$ 

TYPICAL PERFORMANCE CHARACTERISTICS

Fig. 4 Cathode Current vs. Cathode Voltage




Fig. 5 Cathode Current vs. Cathode Voltage




Fig. 6 Change In Reference Input Voltage vs. Cathode Voltage




Fig. 7 Dynamic Impedance Frequency




Fig. 8 Small Signal Voltage Amplification vs. Frequency





Fig. 9 Pulse Response



TYPICAL APPLICATIONS

Fig. 10 Shunt Regulator




Fig.11 Output Control
for a Three-Terminal
Fixed RegulatorFig.12 High Current
Shunt Regulator

Fig. 13 Current Limit or Current Source




Fig. 14 Constant-Current Sink

